

# iBOX 1300/D4 Series

iBOX-1365UE/D4, iBOX-1345UE/D4, iBOX-1315UE/D4

Fanless Embedded BOX PC



## KEY FEATURES

- Intel® 13th Gen (Raptor Lake-P) Core™ Processors
- 2 x 260-pin SO-DIMM up to 64GB DDR4 3200 MHz
- 1 x USB4, 5 x USB3.2 Gen2, 2 x USB 2.0, 1 x M.2 Key M, 1 x M.2 Key E, 1 x COM, 1 x SATA3
- 2 x Intel 2.5 Gigabit LAN
- Supports Quad display, 1 x HDMI 2.0b, 3 x DP 1.4a (2 from Type C)
- Supports Intel® vPro, AMT (iBOX-1365UE/D4, iBOX-1345UE/D4)
- TPM 2.0 onboard IC
- 19V/90W Power Adapter
- 171.8 x 50.05 x 109.45 mm, Fanless Embedded BOX PC

## SPECIFICATIONS

### Processor System

CPU	iBOX-1365UE/D4 (i7-1365UE, 2P+8E) iBOX-1345UE/D4 (i5-1345UE, 2P+8E) iBOX-1315UE/D4 (i3-1315UE, 2P+4E)
Chipset	MCP
BIOS	AMI SPI 256 Mbit

### Memory

Technology	Dual Channel DDR4 3200 MHz
Capacity	64GB (32 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

### Graphics

Controller	Intel® Iris® X <sup>e</sup> Graphics for i7/i5 CPU Intel® UHD Graphics for i3 CPU
HDMI	HDMI 2.0b Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.4a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Quad-Display (Included 2 outputs from Type-C)

### Expansion Slot

M.2	1 x M.2 (Key E, 2230) with PCIe x1, USB 2.0 and CNVi for Wireless
-----	---

### Audio

Interface	Realtek ALC233/ALC256, High Definition Audio.
-----------	---

### Ethernet

Controller/ Speed	iBOX-1365UE/D4, iBOX-1345UE/D4: Intel® I226LM with 10/100/1000/2500 Mbps, supports AMT/vPro iBOX-1315UE/D4: Intel® I226LM with 10/100/1000/2500 Mbps
Connector	2 x RJ-45

### Storage

M.2	1 x M.2 (Key M, 2242/2260/2280) with PCIe Gen4 x4 for SSD *M.2 Key M 2280(Supported by bracket)
SATA	1 x SATA3.0 (6.0 Gb/s)

### Front I/O

USB	2 x USB 3.2 Gen2 (Type A) 1 x USB4/Thunderbolt™ 4 (Supports DP1.4a display output) 1 x USB 3.2 Gen2 (Type-C, Support DP1.4a display output) 2 x USB 2.0
Audio	1 (headphone & microphone jack)

### Rear I/O

HDMI	1 x HDMI 2.0b
DisplayPort	1 x DP1.4a
Ethernet	2 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type-A)
DC Jack	1
COM	1 x COM(RS-232)

### Watchdog Timer

Output Interval	From Super I/O to drag RESETCON# 256 Segments, 0, 1, 2, ...255sec
-----------------	--

### Power Requirements

Input PWR Power On	12V~19V DC-In Jack AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready
--------------------	---

### Environment

Operating Temp	0°C ~ 40°C
Storage Temp	-40° C – 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

### Mechanical

Construction	Aluminum
Mounting	VESA mounting, Wall mounting, Din-rail (By request)
Dimensions (W x H x D)	171.8 x 50.05 x 109.45 mm
Weight	Net Weight:1.6Kg

### Others

OS Support	Windows 10/11
TPM	TPM 2.0 onboard IC
Certifications	CE, FCC
Packing List	1 x 19V/90W Power Adapter 1 x Screw Package 1 x Wall mount kit