





iCF 1IE2 series

Drawing



Specifications

Interface	PATA
Flash Type	iSLC
Capacity	4GB~128GB
Max. Channels	2
Sequential R/W (MB/sec, max.)	85/55
Max. Power Consumption	0.60 W
Thermal Sensor	√
H/W Write Protect	Optional*
ATA Security	√
S.M.A.R.T.	√
Dimension (WxLxH)	42.8X 36.4 X 3.3 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -40°C ~ +85°C MTBF: 3 million hours

Ordering Information

Operation Temp.	4GB	8GB	16GB	32GB	64GB	128GB
Standard Grade (0°C ~ +70°C)	DHCFC-04GYA2BC1SC(W)	DHCFC-08GYA2BC1SC(W)	DHCFC-16GYA2BC1DC(W)	DHCFC-32GYA2BC1DC(W)	DHCFC-64GYA2BC1DC(W)	DHCFC-A28YA2BC1DC(W)
Industrial Grade (-40°C ~ +85°C)	DHCFC-04GYA2BW1SC(W)	DHCFC-08GYA2BW1SC(W)	DHCFC-16GYA2BW1DC(W)	DHCFC-32GYA2BW1DC(W)	DHCFC-64GYA2BW1DC(W)	DHCFC-A28YA2BW1DC(W)

*H/W write protect function is optional.

For the write protect demand, please place the order by PN: DHCFC-xxxYA2Bx1xCW