



OFM-21W00

21.5" Full-HD PCAP Multi-Touch Fanless Open Frame Monitor

- > 21.5" Full-HD Open frame PCAP Touch Monitor
- > VGA, Display Port, HDMI input connectors
- > Audio phone jack in
- > USB type A for touch function
- > Slim & Strength Design
- > Fanless Operation from 0° ~ 45°C
- > 12V DC in (Option for wide voltage 9~36V DC in)
- > Various mounting kits compliance with OFT series

+ Spec

Panel	
LCD Size	21.5", 16:9
Display Type	Full HD
B/L Inverter/Converter	LCD built in
Resolution	1920 x 1080
Pixel pitch	0.24795(H) x 0.24795(V)
Luminance	250 cd/m ²
Contrast ratio	2000
Viewing angle	89 (U), 89 (D), 89 (L), 89 (R)
Response time	35 ms
Backlight	LED
Touch Type	Projective Capacitive Multi-Touch supports up to 10 points
Touch Light Transmission	89 %
Touch Controller	EETI
I/O	
HDMI	1x HDMI input
Display Port	1x Display Port input
VGA	1x VGA input
System Control	
LED Indicator	Power Led
Control Buttons	OSD Function Key (Power/ Menu/ Up/ Down)
Certifications	
Certification Information	CE / FCC Class A
Mechanical & Environmental	
Operating Temperature	0°C ~ 45°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H)	501.9 x 294.2 x 53.4 mm
Weight	3.5Kgs
Vibration Test	1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 0.5hr/axis
Shock Test	Operating: IEC 60068-2-27 testing procedures, 10G for operation mode
Mounting Kit	Option for Flush / Panel / Wall Mount with mounting kits
VESA	75 x 75 mm 100 x 100 mm
Power Requirement	+12V DC in
System Fan	Fanless
Relative Humidity	0~90% Relative Humidity, Non-condensing
Fanless	Yes
Drop	ISTA 2A, IEC-60068-2-32 Test:Ed
Ordering Information	
Ordering Information	OFM-21W00-X0003-0R 21.5" Full-HD Multi Touch Open Frame Monitor, w/VGA/HDMI/DP/OSD key/Speaker/12V power adapter ACC-OFT-21-FMT-01R Flush Mount Kits for OFT-21W series ACC-OFT-21-PMT-01R Panel Mount Kits for OFT-21W series ACC-OFT-21-WMT-01R Wall Mount Kits for OFT-21W series