

R19IT7T-OFA1

19" Intel® Core™ i5 (Tiger Lake) Open Frame Panel PC



KEY FEATURES

- Intel® Core™ Tiger Lake UP3 i5-1135G7 (Without vPro) / Intel® Core™ Tiger Lake UP3 i5-1145G7E (With vPro)
- 1280x1024 Resolution
- Multi display supports DP / HDMI / LVDS / eDP panel interface
- Multiple I/Os, 2 x Serial Ports, 4 x USB 3.2 Gen. 1 Ports
- 12V Single Voltage Power Input



SPECIFICATIONS

Display			
Resolution	1280x1024	Size	19.0 inches
Contrast Ratio	1000:1	Panel Brightness	400.0 nits
View Angles	85,85,80,80	Active Area	376.32x301.06 mm
Touch / Glass	Resistive Touch Screen (Optional) Protection Glass Without Touch Function (Optional)		
System Specification			
WLAN	Support (Optional)	BT	Support (Optional)
Processor	Intel Core i5-1135G7 2.4GHz (up to 4.2GHz)	Memory	1 x SO-DIMM, DDR4 3200 MHz, 4GB 8GB (Optional) 16GB (Optional) 32GB (Optional) 2 x SO-DIMM, DDR4 3200 MHz, 4GB (Optional) 8GB (Optional) 16GB (Optional) 32GB (Optional) 64GB (Optional)
Storage	1 x M.2 M-Key 2242 SATA SSD or 1 x M.2 M-Key 2280 NVMe SSD 128GB 256GB (Optional) 512GB (Optional) 1TB(for NVMe) (Optional) 2TB(for NVMe) (Optional) 4TB(for NVMe) (Optional) 1 x SATA III , up to 2TB (Optional)	Ethernet controller	2 x Intel® Ethernet Controller
Security	TPM 2.0	Operating System	Windows 11 IoT Enterprise SAC (64 bit) (Optional) Windows 11 Pro 64 bit (Optional) Windows 10 IoT Enterprise (64 bit) (Optional) Linux Ubuntu 22.04 (Optional)
Mechanical			
Dimension	445 x 355 x 71 mm	Mounting	Open Frame Panel Mount VESA Mount
Enclosure	Metal Housing	Cooling System	Fanless design
Environment			
Operating Humidity	10% to 90% RH, Non-Condensing	Operating Temperature	0°C to 50°C

Storage Temperature -10°C to 60°C

Certification

Certification CE, FCC

IO Ports

Power Input 1 x 12V DC, Din4 pin connector

USB Port 4 x USB3.2 Gen2x1 (Type-A)

Serial Port 1 x RS232/422/485 (Default RS232)
1 x RS232

Video 1 x DP1.4
1 x HDMI 2.0 (Optional)

Audio Mic in
Line out

Expansion Port 1 x M.2 2242/2280 Key M slot for SATA/NVMe SSD
1 x M.2 2230 Key E slot for WiFi (Optional)

LAN 2 x Giga LAN RJ45 Connector

Indicator 1 x LED Indicator for power
1 x LED Indicator for storage

Brightness Knob 1 x Brightness Adjustment Knob

Control

Button 1 x Power Button
1 x Reset Button

Accessory

Accessory 100~240V AC to DC Adapter
Power Cord
VESA screws

Power

Power Rating 12V DC

Adapter 12V 120W

DIMENSIONS UNIT:MM

