

## AFL4-W101-ADLP

10.1" Fanless Panel PC with Intel® Alder Lake-P Core™ Processor



## Features

- » Intel® Alder Lake-P Platform
- » New narrow bezel design
- » Anti-glare and Anti-UV PCAP
- » Support Gloved and Wet Hand Operation
- » Support WiFi 6E and Bluetooth®5.2

## Specifications

|                          |  |
|--------------------------|--|
| System                   |  |
| CPU                      | 12th Gen Intel® Core™ Mobile i7/i5/i3 Processors (Alder Lake-P)                            |
| On-board Memory          | Dual channel On board LPDDR4X 8G   |
| Communication            |  |
| Wireless                 | IEEE 802.11ax 2T2R module (Wi-Fi 6E)<br>with BT v5.0 (M.2 2230 A-key)                      |
| I/O Interface            |  |
| Ethernet                 | LAN1: Intel® I225V 2.5GbE controller<br>LAN2: Intel® I225-LM 2.5GbE controller (Intel AMT) |
| Audio                    | AMP 1.2W (internal speaker)  |
| Expansion                | 1 x M.2 M key 2242 (PCIe Gen4 x 4)<br>1 x M.2 M key 2280 (PCIe Gen4 x 4)                   |
| Audio Codec              | Realtek ALC888S  |
| Power                    |  |
| Input                    | 12V DC   |
| Environment              |  |
| Operating Temperature    | -10°C ~ 50°C   |
| Safety & EMC             | CE/EMC , FCC , RED (Class A)   |
| Humidity                 | 10% to 95% (non-condensing)  |
| Storage Temperature      | -20°C ~ 60°C   |
| IP Level                 | Front panel IP65   |
| Physical Characteristics |  |
| Color                    | Silver+Black   |
| Mounting                 | Wall, Rack, Stand, ARM, VESA100  |
| Construction Front Panel | Aluminum die casting+SECC  |
| LCD                      |  |
| Size                     | 10.1"  |
| Resolution               | 1280 x 800 (16:10)   |
| Brightness (cd/m2)       | 350(cd/m²)   |
| Contrast Ratio           | 900:1  |
| Viewing Angle (H-V)      | 170°/170°  |
| Backlight MTBF           | 30000 hours  |
| Touch                    |  |
| Touch Screen             | Multi-point projected capacitive type  |

|                      |  |
|----------------------|--|
|                      | (anti-UV / anti-glare coating, support gloves) |
|                      | Surface hardness: ≥ 7H                         |
| Touch Controller     | EETI EXC 81 Series                             |
| <b>I/O Interface</b> |  |
| I/O Interface        | 2 x RS-232 (by DB9)                            |
|                      | 2 x RS-232/422/485 (by DB9)                    |
|                      | 2 x LAN  |
|                      | 1 x DC Input Jack                              |
|                      | 1 x Reset Button                               |
|                      | 1 x Power Switch                               |
|                      | 1 x AT/ATX switch                              |
|                      | 2 x USB 3.2 Gen1x1                             |
|                      | 1 x USB2.0                                     |
|                      | 1 x HDMI (up to 3840*2160 @30Hz)               |
|                      | 2 x LAN (Intel® I225V 2.5GbE controller)       |
|                      | 2 x USB 3.2 Gen2                               |
| <b>OS Support</b>    |  |
| OS Support           | Windows 10 IoT                                 |
|                      | Linux  |

## Ordering Information

|                          |  |
|--------------------------|--|
| AFL4-W101-ADLP-i7/8G-R10 | 10.1" 350cd/m <sup>2</sup> 1280x800 fanless panel PC with Intel® Core™ i7-1260P on-board processor, 8GB LPDDR4x on-board, Wi-Fi 6E and Bluetooth 5.2 module, PCAP touch, 12V DC, R10 |
| AFL4-W101-ADLP-i5/8G-R10 | 10.1" 350cd/m <sup>2</sup> 1280x800 fanless panel PC with Intel® Core™ i5-1240P on-board processor, 8GB LPDDR4x on-board, Wi-Fi 6E and Bluetooth 5.2 module, PCAP touch, 12V DC, R10 |
| AFL4-W101-ADLP-i3/8G-R10 | 10.1" 350cd/m <sup>2</sup> 1280x800 fanless panel PC with Intel® Core™ i3-1220P on-board processor, 8GB LPDDR4x on-board, Wi-Fi 6E and Bluetooth 5.2 module, PCAP touch, 12V DC, R10 |

## Packing List

|                     |                |
|---------------------|----------------|
| 1 x AFL4-W101-ADL-P | 1 x Power Cord |
| 1 x Power Adapter   | 1 x QIG        |